



SYNTHETIC GEAR LUBRICANT

Pure Estorlin® Marine 80W/90 Lower Unit Gear

- Engineered to provide maximum protection for sterndrive and outboard lower units
- Keeps moisture in suspension in cases of water intrusion
- Excellent protection against corrosion and excessive wear
- Protects gears from metal to metal contact
- Perfect for hi-speed and hi-horsepower applications
- Meets and exceeds manufacturers requirements



CHARACTERISTICS

Pour Point -20°F
Flash Point 480°F
Viscosity @ 100°C 13.50 cSt Min 18.50 cSt Max **15.20 cSt Typical**
Product Color Red
Chemical 100% Pure Synthetic

CERTIFICATIONS

API Specification GL-5

DIRECTIONS

Fill gear cases from the drain hole until it reaches manufacturers full level. Change gear case lube every 50 hours or annually per most manufacturers' recommendation.

COMPATIBILITY

Will blend with OEM oils and most synthetics

PART NUMBERS

KE-380	10 QT CASE
KE-380 30 GL	30 GAL DRUM
KE-380 55 GL	55 GAL DRUM

RECOMMENDED APPLICATIONS

Marine
Sterndrive & Outboard Gear Cases

Klotz Synthetic Lubricants
Fort Wayne, IN USA

Order Online: at klotzlube.com
Tech Line: 260.490.0489

Order Line: 800.242.0489
Email: salesteam@klotzlube.com

©2018 Klotz SL, Inc Tech Sheet